

Technical data sheet

Earth rod for standard applications

Item number: 5000769



- High corrosion resistance
- Zinc support approx. 130 µm
- With peg and bore for linking together
- Round pegs with three knurls
- Conforms to the requirements according to VDE 0185-305 (IEC 62305) and DIN EN 62561-2
- Short-circuit current I_k (50 Hz), time 1 s, temp. max. 300 °C: 12.3 kA



St Steel

FT Hot-dip galvanised

Master data

Item number	5000769
Description 1	Earth rod
Description 2	standard
Manufacturer	OBO
Dimension	1,5m
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	5
Unit of quantity	Piece
Weight	573 kg
Weight unit	kg/100 pc.
CO Footprint (GWP) Cradle-to-Gate	11,3337 kg CO _e / 1 Piece


Technical data sheet

Earth rod for standard applications

Item number: 5000769



Dimensions



Length 1,500 mm

Technical data

Version for	Miscellaneous
Design earth rod	Standard
Lightning current carrying capacity	H/100 kA
Short-circuit current (50 HZ)(1 s; $\leq 300^{\circ}\text{C}$)	12.3 kA
Profile type	Round D=25 mm
Connection type	With pin/drill hole