### **Technical data sheet** Spacer clip 732 FT

**Item number: 1362364** 





Spacer clip for the installation of pipes and cables on walls, ceiling and floors. With self-locking upper part. Surfaces G and FT from a clip size of 20 are suitable for installation with a nail device or a bolt-firing tool.

Approved for the maintenance of electrical function according to DIN 4102 Part 12, maintenance of electrical function classes E30 to E90.



St

Steel



Hot-dip galvanised

#### Master data

Item number	1362364
Description 1	Distance saddle
Description 2	with threaded connection M6
Manufacturer	OBO
Dimension	12-14mm
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	25
Unit of quantity	Piece
Weight	1.729 kg
Weight unit	kg/100 pc.
CO Footprint (GWP) Cradle-to- Gate	0,0538 kg COe / 1 Piece

## **Technical data sheet** Spacer clip 732 FT





# 

41 mm
29 mm
18 mm
14 mm
14 mm
12 mm
6.5 mm
1.25
1.25
3 mm

#### Technical data

M6

Distance to the wall	yes
Number of cables/pipes	1
Version for	Closed
Fastening type	Threaded connection
For diameter	12 - 14
Suitable in fire protection area	yes
Halogen-free	yes
Plastic-covered	no
Material thickness	1.25 mm
Clamping range D, max.	14 mm
Clamping range D, min.	12 mm
UV-resistant	yes