

Technical data sheet

BZ3 bolt tie

Item number: 3498683



Bolt tie BZ3 for the anchoring of medium-duty to heavy-duty loads, both in cracked and non-cracked concrete. Suitable for heavy loads with small edge and axial distances. For knocking in.

European Technical Approval ETA-19/0619, including characteristic values under fire ex-

posure to fire resistance R 120.

Proof of suitability in the event of seismic impacts, categories C1 and C2.

Shock approval by the Federal Office for Civil Protection in Bern, Switzerland.
* With large washer to DIN EN ISO 7093-1 (DIN 9021)



St Steel

G Electrogalvanized

Master data

| | |
|---------------------|----------------------------|
| Item number | 3498683 |
| Type | BZ3 8x75/0-20 |
| Description 1 | Wedge anchor BZ3 |
| Description 2 | with large washer |
| Available from | 01.04.2023 |
| Manufacturer | OBO |
| Dimension | M8x75 |
| Material | Steel |
| Surface | Electrogalvanized |
| Surface standard | EN ISO 19598 / EN ISO 4042 |
| Smallest sales unit | 50 |
| Unit of quantity | Piece |
| Weight | 3 kg |
| Weight unit | kg/100 pc. |


Technical data sheet

BZ3 bolt tie

Item number: 3498683



Dimensions



| | |
|-------------|-------|
| Length | 75 mm |
| Dimension L | 75 mm |

Technical data

| | |
|-------------------------------------|------------------|
| Version for | For knocking in |
| Anchor/nail/bolt version | Spreading anchor |
| Drill hole diameter, max. | 8 mm |
| Drill hole diameter, min. | 8 mm |
| Thread | M8 |
| Thread metric | 8 |
| Thread type | Metric |
| Thread length | 33 mm |
| WAF | 13 |
| Approvals available | yes |
| Mounting type, anchor, tie | Pre-mounting |
| Tie screw system | Hexagon head |
| Clamping range, max. | 20 mm |
| Clamping range, min. | 0 mm |
| Thread, imperial | 5/16" |
| Fire protection class to EN 13501-2 | Other |
| ETA earthquake rating | C1 and C2 |