Technical data sheet

CML3518 profile rail, slot 17 mm, FT, perforated



Item number: 1104568



Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.











St

Steel


FT

Hot-dip galvanised

Master data

Item number	1104568
Description 1	Profile rail
Description 2	perforated, slot 17mm
Manufacturer	OBO
Dimension	1000x35x18
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	10
Unit of quantity	Metre
Weight	73.6 kg
Weight unit	kg/100 m

Dimensions



Length	1,000 mm
Width	35 mm
Height	18 mm
Dimension L	1,000 mm

Technical data sheet

CML3518 profile rail, slot 17 mm, FT, perforated



Item number: 1104568

Technical data		
	Breakable	no
	Type of perforation	Perforated back
	Version for	Single profile
	Maintain electrical functions	yes
	Material thickness	1.25 mm
	With perforation	no
	With toothing	no
	Profile shape	C profile
	Slot width	17 mm
	Static value A	0.88 cm ²
	Static value ly	0.41 cm
	Static value Iz	1.81 cm
	Static value Wy	0.41 cm ²
	Static value Wz	1.03 cm ²