

# Technical data sheet

## CML3518 profile rail, slot 17 mm, A2, perforated

Item number: 1104501



Central C profile rail for cable routing, in conjunction with clamp clips with a hammerhead foot. Can also be used as suspension construction for cable support systems.



**A2** Stainless steel

**2B** Bright, treated

### Master data

Item number	1104501
Type	CML3518P2000A2
Description 1	Profile rail
Description 2	perforated, slot 17mm
Manufacturer	OBO
Dimension	2000x35x18
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	2
Unit of quantity	Metre
Weight	71 kg
Weight unit	kg/100 m


# Technical data sheet

CML3518 profile rail, slot 17 mm, A2, perforated



Item number: 1104501

## Dimensions



Length	2,000 mm
Width	35 mm
Height	18 mm
Dimension L	2,000 mm

## Technical data

Breakable	no
Type of perforation	Perforated back
Version for	Single profile
Drill hole spacing, centre	25 mm
Bundle	20 m
Maintain electrical functions	no
Material thickness	1.25 mm
With perforation	yes
With tothing	no
Profile shape	C profile
Slot width	17 mm
Static value A	0.88 cm <sup>2</sup>
Static value Iy	0.41 cm
Static value Iz	0.41 cm
Static value Wy	1.81 cm <sup>2</sup>
Static value Wz	1.03 cm <sup>2</sup>