Technical data sheet

Cable carrier trough, single, for individual routing





Cable support brackets for quick and easy routing of cables in areas where common cable support systems cannot be installed due to lack of space. The cable support brackets possess a large load-bearing surface as well as rounded outer edges to protect the cables.

In accordance with DIN VDE 0298-300, a maximum support spacing of 0.8 m should not be exceeded.



(€

St

Steel



Hot-dip galvanised

Master data


Item number	6006890	
Туре	KTW 100 FT	
Description 1	Cable support trough	
Description 2	for single routing	
Manufacturer	OBO	
Dimension	44x200x113	
Colour	zinc	
Material	Steel	
Surface	Hot-dip galvanised	
Surface standard	DIN EN ISO 1461	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	48 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	1,2123 kg CO2e / 1 Piece	

Technical data sheet

Cable carrier trough, single, for individual routing



Item number: 6006890



4	*******		
	Height	44 mm	
	Plate thickness	2 mm	
198			
To built of data			
Technical data			
	Number of troughs	0 St.	
	Version for	Single	
	F in kN per trough	0.35 kN	
	With fastening material	no	
	Adjustable	no	