

Technical data sheet

Central hanger for cable tray, side height 60 mm FS

Item number: 6358720



Centre suspension for cable trays with rolled side rail of side height 60 mm. The centre suspension possesses a rotatable M10 threaded sleeve. When filling, ensure an even distribution of the load (avoid one-sided filling).

The widths 100, 150 and 200 mm have additional base perforations, in order to screw the centre suspensions to the tray base when used for the maintenance of electrical functionality according to DIN 4102 Part 12.



St	Steel
FS	Strip galvanized

Master data

Item number	6358720
Type	MAH 60 400 FS
Description 1	Centre suspension
Description 2	for cable tray
Manufacturer	OBO
Dimension	B400mm
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	46 kg
Weight unit	kg/100 pc.
CO Footprint (GWP) Cradle-to-Gate	1,1823 kg COe / 1 Piece


Technical data sheet

Central hanger for cable tray, side height 60 mm FS

Item number: 6358720



Dimensions



Length	40 mm
Width	400 mm
Height	57 mm
Dimension B	395 mm
Dimension b	384 mm

Technical data

Version for	Suspended
F in kN	0.1 kN
Maintain electrical functions	no
for width max.	400 mm
for width min.	400
Suitable for metric threaded rod	10
Suitable for mesh cable tray	no
Suitable for cable ladder	no
Suitable for cable tray	yes
Suitable for tray/ladder width	400 mm
Hole diameter	10.5 mm
Adjustable	no