

# Technical data sheet

## US 3 suspended support FSK black

Item number: 7265696



Suspended support (U profile) in the dimensions of 50 x 30 mm with welded-on head plate. For fastening to horizontal concrete ceilings and steel girders. Powder-coated in jet black (RAL 9005) From a bracket width of 400 mm or when the bracket is mounted on the end of the suspended support, it is recommended to use the spacer type DSK 25.



**St** Steel

**P135** PES135 - Polyester

### Master data

Item number	7265696
Description 1	Support
Description 2	with welded head plate
Manufacturer	OBO
Dimension	50x30x400
Colour	Jet black; RAL 9005
Material	Steel
Surface	PES135 - Polyester
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	75 kg
Weight unit	kg/100 pc.


# Technical data sheet

US 3 suspended support FSK black

Item number: 7265696



## Dimensions



Length	400 mm
Length	1.31 ft
Width	50 mm
Height	30 mm
Plate thickness	0.08 in
Dimension L	400 mm

## Technical data

Version for	U profile
Bracket length 200	2.7 kN
Bracket length 400	1.5 kN
Maintain electrical functions	no
Material thickness	2 mm
Maximum tensile load	5 kN