

Technical data sheet

UTC3 W with 3 protective contact sockets, white

Item number: 7404611



The ready-for-connection UTC3 universal support possesses 3 pre-installed 33° protective contact sockets in white of 16 A. Suitable for VL connection cables and device installation units of nominal size 2, 4, R4, 6 and R7.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI.
The ready-for-connection UTC3 universal support has 3 pre-installed 33° protective contact sockets in white with 16 A.

PVC connection cable with connector, 3-pin, type WINSTA® MIDI




PA Polyamide

Master data

Item number	7404611
Description 1	Universal supportConnectWINSTA
Description 2	VDE, triple white
Manufacturer	OBO
Dimension	165x76x45
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	29.9 kg
Weight unit	kg/100 pc.

Dimensions



Length	175 mm
Width	76 mm
Height	60 mm

Technical data sheet

UTC3 W with 3 protective contact sockets, white

Item number: 7404611



Technical data

Connection cable, halogen-free	yes
Number of installable devices	3
Version for	Triple pure white
Cable length	300 mm
Line cross-section	2.5 mm ²
Plug-in system	WINSTA® MIDI
Plug connector system, system-specific	yes
Circuit	1
System length	165 mm
Surge protection	no