

Technical data sheet

Combination arrester V25 3-pole 280 V with acoustic signalling

Item number: 5097185



Combination arrester consisting of lightning current and surge arrester type 1+2

- Complete unit consisting of upper part and base, pre-mounted and ready for connection
- Suitable for TN network systems
- With audible signalling for function monitoring, signal tone can be turned off with 24 h repeat
- Plug-in arrester with dynamic cut-off unit
- Visual function display
- Voltage protection level < 900 V
- Encapsulated, non-extinguishing zinc oxide varistor arrester for use in standard distributor housings
- Labelled connections

Application example: Buildings with open-wire power supply.

*Complete = cover and base

With audible alarm system



Master data

Item number	5097185
Type	V25-B+C 3+AS
Description 1	CombiController V25
Description 2	with acoustic signalling
Manufacturer	OBO
Dimension	280V
Smallest sales unit	1
Unit of quantity	Piece
Weight	50.5 kg
Weight unit	kg/100 pc.

Technical data sheet

Combination arrester V25 3-pole 280 V with acoustic signalling

Item number: 5097185



Technical data

Arrester surge current (8/20 µs) [total]	90 kA
Response time	<25 ns
Blow-out	no
Version for	3-pole with AS
Pole version	3
Structural width in division units (division unit, 17.5 mm)	4
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Lightning surge current (10/350 µs)	7 kA
Lightning surge current (10/350)	21 kA
Remote signalling	no
Maximum continuous voltage AC	280
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	2.5 mm ²
Lightning protection zone LPZ	0→2
Max. mains-side overcurrent protection	160
Maximum back-up fuse	160 A
Maximum discharge current (8/20 µs)	50 kA
Nominal discharge current (8/20 µs)	30 kA
Nominal voltage AC (50/60 Hz)	230 V
Network form	Other
TN network form	yes
TN-C network form	yes
Pole number	3
Protection rating	IP20
Protection level	≤0,9
Signalling on device	Optical and acoustic
SPD to EN 61643-11	Type 1+2
SPD to IEC 61643-1	Class I+II