

Technical data sheet

Cone cable gland, PG thread, light grey

Item number: 2036215



Standard cable gland, shape A, to DIN 46320 with simple NR/SBR sealing ring.
PG connection thread in accordance with DIN 40430.

Protection rating: with connection thread sealing ring IP65, without connection thread sealing ring IP54.

Note: Only tighten polystyrene cable glands lightly due to the risk of stress crack formation.

Shock-resistant



PS Polystyrene

Master data

| | |
|---------------------|----------------------|
| Item number | 2036215 |
| Description 1 | Cable gland |
| Manufacturer | OBO |
| Dimension | PG21 |
| Colour | Light grey; RAL 7035 |
| Material | Polystyrene |
| Smallest sales unit | 50 |
| Unit of quantity | Piece |
| Weight | 1.76 kg |
| Weight unit | kg/100 pc. |

Technical data sheet

Cone cable gland, PG thread, light grey

Item number: 2036215



Dimensions



| | |
|------------------|---------|
| Length | 37.5 mm |
| Width | 37.5 mm |
| Height | 48 mm |
| Dimension D1 | 18 mm |
| Dimension D2 | 37.5 mm |
| Dimension D3 | 21.2 mm |
| Dimension D4 | 21 mm |
| Dimension G | Pg21 mm |
| Dimension L max. | 38 mm |
| Dimension L1 | 10 mm |
| Dimension L2 | 19 mm |
| Dimension L3 | 7 mm |
| Dimension L4 | 17 mm |

Technical data

| | |
|--------------------------|--------------|
| Type of seal | Sealing ring |
| Version for | Straight |
| Bend protection | no |
| Sealing area D, max. | 18 mm |
| Sealing area D, min. | 14 mm |
| explosion-proof | no |
| For Ex zone | Without |
| For Ex zone gas | Without |
| For Ex zone dust | Without |
| Thread | Pg 21 |
| Thread type | PG |
| Thread length | 11 mm |
| Nominal thread size | 21 |
| Fibre-glass reinforced | no |
| Halogen-free | yes |
| Sealing insert, multiple | no |
| With locknut | no |
| Impact-resistant | no |
| WAF 1 | 33 mm |
| WAF 2 | 30 mm |
| Protection rating | IP65 |
| Splittable gland | no |
| Strain relief option | no |