

Technical data sheet

Lightning barrier FLD

Item number: 5098940



The type VF FLD 60T S lightning barrier is a surge arrester/fine power protection type 3 to DIN EN 61643-11 for protecting end devices from transient surge voltages.

The protection devices are used for mounting on DIN profile rails near to devices to be protected and are designed for DC and AC systems.



Master data

Item number	5098940
Type	FLD 60T S
Description 1	Lightning barrier
Description 2	with decoupling inductivity
Manufacturer	OBO
Dimension	230V
Smallest sales unit	1
Unit of quantity	Piece
Weight	4.4 kg
Weight unit	kg/100 pc.

Technical data sheet

Lightning barrier FLD

Item number: 5098940



Technical data

Response time	<1 ns
Structural width in division units (division unit, 17.5 mm)	1
Operating temperature, max.	80 °C
Operating temperature, min.	-40 °C
Explosion-tested version	no
Remote signalling	no
Maximum continuous voltage AC	160
Maximum continuous voltage DC	230
Inductivity	100 µH
Conductor cross-section, rigid (single-wire/multiwire), max.	2.5 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	0.14 mm ²
Lightning protection zone LPZ	2→3
Installation type	DIN rail 35 mm
Nominal discharge current (8/20 µs)	10 kA
Nominal voltage AC (50/60 Hz)	60 V
Network form	Other
OBO_Nominal load current (input/ output terminal)	0.47 A
Protection rating	IP20
Protection level wire-wire	<300 V
Protection level wire-earth	<500 V
Signalling on device	Without