

# Technical data sheet

## Heavy-duty vertical cable ladder SLM 50, 3 m C40

Item number: 6010547



The vertical ladder with a 50 mm side height is shipped in an unmounted state and must be screwed together on the construction site.

The appropriate clamp clip for the C profile rung is type 2056U.



**St** Steel

**FT** Hot-dip galvanised

### Master data

Item number	6010547
Type	SLM 50 C40 10 FT
Description 1	Vertical ladder heavyweight
Description 2	with C 40 rung
Manufacturer	OBO
Dimension	1000x3000
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	3
Unit of quantity	Metre
Weight	793.5 kg
Weight unit	kg/100 m


# Technical data sheet

## Heavy-duty vertical cable ladder SLM 50, 3 m C40

Item number: 6010547



### Dimensions



Length	3,000 mm
Width	1,000 mm
Height	50 mm
Dimension B	1,000 mm
Rung slot dimension	18.00

### Technical data

Side wall version	U profile
Version of the rungs	Profile unperforated
Maintain electrical functions	no
Rustproof steel, pickled	no
Side perforation	yes
Rung distance	600 mm
Rail thickness	2.5 mm