

Technical data sheet

US 3 support A4

Item number: 6342485



U support in fixed lengths. Dimensions 30 x 50 mm.
For bracket widths of 400 mm or more, or if the bracket is mounted at the end of a suspended support, we recommend the use of the spacer, type DSK 25.



A4 Stainless steel

2B Bright, treated

Master data

| | |
|---------------------|--------------------|
| Item number | 6342485 |
| Type | US 3 30 A4 |
| Description 1 | U support |
| Description 2 | 3-sided perforated |
| Manufacturer | OBO |
| Dimension | 50x30x300 |
| Material | Stainless steel |
| Surface | Bright, treated |
| Surface standard | |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 40 kg |
| Weight unit | kg/100 pc. |


Technical data sheet

US 3 support A4

Item number: 6342485



Dimensions



| | |
|-----------|---------------|
| Dimension | 30 x 50 x 2,0 |
| Length | 300 mm |
| Width | 50 mm |
| Height | 30 mm |

Technical data sheet

US 3 support A4

Item number: 6342485



Technical data

| | |
|-------------------------------|----------------------|
| Breakable | no |
| Type of perforation | 3 sides perforated |
| Version for | Single profile |
| Maintain electrical functions | no |
| Material thickness | 2 mm |
| With tothing | no |
| Profile shape | U profile |
| Static value A | 1.42 cm ² |
| Static value Iy | 1.52 cm |
| Static value Iz | 5.72 cm |
| Static value Wy | 0.7 cm ² |
| Static value Wz | 2.29 cm ² |